08813 Magic 2 WiFi 6



Mesh Wi-Fi 6 | SOCKET | 2x GB LAN | 2400MBIT/S

Manufacturer: DEVOLO

Description

- Wi-Fi with Mesh
- OFDMA and MU-MIMO Technology
- Up to 2400 Mbps
- 2x Gigabit LAN
- Range up to 500 meters

The Magic 2 WiFi 6 revolutionises the Wi-Fi speed in your home! With 50 percent more Wi-Fi power than any Wi-Fi 5 PLC adapter, it reaches speeds of up to 1800 Mbps and makes this speed available to every user. Thanks to OFDMA, the channels are used with flexibility: Top-notch Wi-Fi for everyone – when sending or receiving and even when there are many users in parallel! Your Internet signal is distributed over Powerline technology at speeds of up to 2400 Mbps, directly over the electrical wiring and to any room. An adapter turns any power socket into an access point for high-performance multi-room Wi-Fi. And multiple devolo Magic adapters connect to each other automatically to form a comprehensive mesh network. For maximum connectivity, Magic 2 WiFi 6 is also equipped with two Gigabit LAN ports. It is the world's fastest Powerline adapter and its top-notch features make it a networking powerhouse for your home. Enjoy powerful mesh Wi-Fi throughout the home – for everyone!

	2x RJ45					
Integrated Socket	Type F (CEE 7/4) Ampacity: 16A Type E (CEE 7/5) Ampacity: 15A Type G (BIS1363) Ampacity: 13A Type J (SEV 1013) Ampacity: 10A					
	Network filter (2-80	MHz, -22 db to -45 db)				
Plug	Type F (CEE 7/4) Type E 4 (CEE 7/1) Type G (851563) Type J (SEV 1011)					
9.6						
Standards	WI-FI 4/5/6 (IEEE 80.	11 a/b/g/n/ac/ax/k/	(1)			
Radios	2,4GHz + 5GHz Dual	Band Dual concurrent				
Channels	52-64 (DFS 100-140 (D	5 GHz 36-48 (Indoor) 52-64 (DIS-TPC) 100-144 (DIS-TPC)				
Channel widths	20/40/80 MHz					
Streams Data rates	2x2 MIMO					
Mode	2,4 GHz up to 574 M 5 GHz up to 1201 MI Arress Point	5 GHz up to 1201 Mbps Access Point				
	ALLER FORM					
owerline Standards	G.hn (HomeGrid For					
Standards Transmission speeds	2400 Mbps (MIMO)	and				
	1200 Mbps (SISO)	1200 Mbps (SISO)				
Range	500 m					
Transmission frequency Mode	2-86 MHz Peer to Peer					
	Feet to Peet					
thernet						
Standards Transmission speeds	IEEE802.3 u/ab/x/az 10/100/1.000 Mbps					
Auto MDI-X	10/100/1,000 Mbps Yes					
QoS	Yes					
IPv4 / IPv6	Yes / Yes					
uttons/LEDs						
Wi-Fi (Button/LED)	Wi-Fi on/off					
	WPS					
Home (Button/LED)	Powerline connection					
Reset (Button)	Reboot Reset Settings					
LEDs switchable	Yes					
oftware features						
Guest Wi-Fi	Yes					
Wi-Fi timing	Yes					
Parental lock	Yes					
Mesh Wi-Fi		Yes				
Airtime Fairness Access Point Steering	Yes					
Wi-Fi encryption	WPA/WPA2/WPA3	ersonal				
WPS	PBC, PIN					
Idministration	Yes (internet browser)					
Device website		r)				
Device website Home Network App	Yes (IOS/Android)					
Device website						
Device website Home Network App	Yes (IOS/Android)					
Device website Home Network App Cockpit software	Yes (IOS/Android)					
Device website Home Network App Cockpit software invironment and physical data Power consumption	Yes (IOS/Android) Yes (Windows/MacO Maximum: 12,4 W Typcial: 8,2 W	S/Linux)				
Device website Home Network App Cockpit software wironment and physical data Power consumption Power supply Temporature (foreage = 0 persting)	Yes (IOS/Android) Yes (Windows/MacC Maximum: 12,4 W Typcial: 8,2 W Stand-By: 2,5 W	S/Linux)				
Device website Home Network App Cockpit software wironment and physical data Power consumption Power supply Temporature (foreage = 0 persting)	Yes (IOS/Android) Yes (Windows/MacC Maximum: 12,4 W Typcial: 8,2 W Stand-By: 2,5 W 196-250 V AC (50 Hz	S/Linux)				
Device website Home Network App Cockpit software invironment and physical data Power consumption	Yes (IOS/Android) Yes (Windows/MacC Maximum: 12,4 W Typcial: 8,2 W Stand-By: 2,5 W 196-250 V AC (50 Hz -25°C to 70°C + 0°C to	\$/Unux) 				
Device website Home Network App Cacipit software Womenment and physical data Power computing Power comply Temperature Demension (mm, withour socket) Ambient conditions	Yes (IOS/Android) Yes (Windows/MacC Maximum: 12.4 W Typoial: 8.2 W Stand-8y: 2.5 W 196-250 V AC (S0 Hz -35°C to 70°C + 0°C to 152 x 76 x 40 10-90% Humidity (n	\$/Unux) 				
Device setuble Home Network App Codget unfavore and physical deta Prover consumption Prover cogoly Temporize Rememing) Diamension (in mm, vathout socket) Ambaiet conditions Warnanty (in years)	Yes (US/Android) Yes (Windows/MacC Masimum: 12,4 W Typola: 8,2 W Stand-8y,25 W 196-250 V AC (50 Hz -25°C to 70°C + 0°C to 152 x 76 x 40 10-90% Humidity (n 3	5/Linux)) o. 60°C on-condensing)				
Device website Home Network App Cacipit software Womenment and physical data Power computing Power comply Temperature Demension (mm, withour socket) Ambient conditions	Yes (IOS/Android) Yes (Windows/MacC Maximum: 12.4 W Typoial: 8.2 W Stand-8y: 2.5 W 196-250 V AC (S0 Hz -35°C to 70°C + 0°C to 152 x 76 x 40 10-90% Humidity (n	5/Linux)) o. 60°C on-condensing)				
Device setuble Home Network App Codget unfavore and physical deta Prover consumption Prover cogoly Temporize Rememing) Diamension (in mm, vathout socket) Ambaiet conditions Warnanty (in years)	Yes (US/Android) Yes (Windows/MacC Masimum: 12,4 W Typola: 8,2 W Stand-8y,25 W 196-250 V AC (50 Hz -25°C to 70°C + 0°C to 152 x 76 x 40 10-90% Humidity (n 3	5/Linux)) o. 60°C on-condensing)				
Device setuble Home Network App Codget unfavore and physical deta Prover consumption Promer supply Temperical Remembing (in mm, without socket) Ambient conditions Warnanty (in years)	Yes (DS:Androix) Yes (Windows/MacC Masimum: 12.4 W Typoia: Ik.2 W Samd By 25 W 196-250 V AC ISO Hz -250°C to 30°C + 40°C to 152 x76 x40 10-005 Humidity (m 3 Documentation: Prin Ethernet cable RMS	Sriinus) b anc an condensing) and Install Flyer NAS	Laz		J. 7. 7. 18.	
Device setuble Home Network App Codget unfavore and physical deta Prover consumption Promer supply Temperical Remembing (in mm, without socket) Ambient conditions Warnanty (in years)	Yes (US/Android) Yes (Windows/MacC Masimum: 12,4 W Typola: 8,2 W Stand-8y,25 W 196-250 V AC (50 Hz -25°C to 70°C + 0°C to 152 x 76 x 40 10-90% Humidity (n 3	5/Linux)) o. 60°C on-condensing)				
Device setuble Home Network App Codget unfavore and physical deta Prover consumption Promer supply Temperical Remembing (in mm, without socket) Ambient conditions Warnanty (in years)	Yes (DS:Androix) Yes (Windows/MacC Mastmum: 12,4 W Typical 8,2 W Stand 8y,2 S W 192-250 VAC IS0 HE 192-250 VAC IS0 HE 192-250 VAC IS0 HE 192-250 VAC IS0 HE 10-805 Humidity (m 3 Determine cable RUSS	5/Linux) 6 40°C In-condensing) 6 del hothil Flyer R45	Multinom Kit	Mesh Starter Kit	Mash Multicom Kit	
Denis website Man Meteroda Ago Cadati uthuwa Manana Manana Nawara usiangi uthuka Nawara usiangi uthuka Nawara usiangi uthuka Nawara (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana)	Yes (OS/Androix) Yes (VM-Modew/MacC Maanman Maanman 19-250 VAC (S04 H 19-250 VAC (S04 H 19-250 VAC (S04 H 10-305 Humidity (M 3 Doomenstation: Primer cable RMS Add on adapter 6813 UK)	5/Linux) 5/Linux 5/Linux 6/Lin	Multiroom Kit 08826 (UK)	Mesh Starter Kit 08931 (UK)	Mesh Multiroom Kit 08935 (UK)	
Denis welker Celapia welkere Celapia welkere Meren search of physical denis Prever search of physical denis de	Ye (GOAradova) Ye (Windown MacC Maansum: 12,4 W Special L2,4 W Lawed by 2,2 W L32,4 76,4 W 19,950 K J000 K (Start) 19,950 K J0	Schwar) Alerc ans condensing) end install Pyer RUSS Stater (R Stater (R Stater (R Stater (R) Stater (R) Stater (R) Stater (R)	Multiroom Kit 08826 (UK) 4250059688261	Mesh Starter Kit 08931 (UK) 4250059689312	Mesh Multiroom Kit 08935 (UK) 4250059689350	
Denis website Man Meteroda Ago Cadati uthuwa Manana Manana Nawara usiangi uthuka Nawara usiangi uthuka Nawara usiangi uthuka Nawara (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana) Manana (Manana)	Ve (GOArdenia) Ver (Windowstkaut Management (2, 4W Standiege 2, 2W Standiege 2	Sclinus) serc en continuing) end install Pyer ULAS States (PA States (PA At 2005)084886	Multiroom Kit 08826 (UK) 4250059688261 1293 g	Mesh Starter Kit 08931 (UK) 4250059689312 1080 g	Mesh Multiroom Kit 08935 (UK) 4250059689350 1470 g	
Denis welker Marken Heterock App Galpit unferener Menorement of physical data Person scoppy Person scoppy (or mm, without scolet) Menorement (or mm, without scolet) Menorement Menorement Accessories EAN Marken Database Da	Ye (GOAradova) Ye (Windown MacC Maansum: 12,4 W Special L2,4 W Lawed by 2,2 W L32,4 76,4 W 19,950 K J000 K (Start) 19,950 K J0	Schwar) Alerc ans condensing) end install Pyer RUSS Stater (R Stater (R Stater (R Stater (R) Stater (R) Stater (R) Stater (R)	Multiroom Kit 08826 (UK) 4250059688261	Mesh Starter Kit 08931 (UK) 4250059689312	Mesh Multiroom Kit 08935 (UK) 4250059689350 1470 g	
Denis website Catajit urbuwe Catajit urbuwe Newer soppit Power soppit	Ve (GOArdenia) Ver (Windowstkaut Management (2, 4W Standiege 2, 2W Standiege 2	Sclinus) serc en continuing) end install Pyer ULAS States (PA States (PA At 2005)084886	Multiroom Kit 08826 (UK) 4250059688261 1293 g	Mesh Starter Kit 08931 (UK) 4250059689312 1080 g	Mesh Multiroom Kit 08935 (UK) 4250059689350	
Denia melani Canajai unimuso Canajai unimuso Preser sananymison Preser sananymison Preser sananymison Preser sananymison Preser sananymison Preser sananymison Preserving Preser	 Yes (G)Andread Yes (Windown Macci Maximum: 124W Yanawa (Yanawa) Yan	Shinuu) serc in condensing) ind Intal Pyre Source (R) Source	Multiroom Kit 08826 (UK) 4250059688261 1293 g 188 x 231 x 92 mm	Mesh Starter Kit 08931 (UK) 4250059689312 1080 g 188 x 231 x 92 mm	Mesh Multiroom Kit 08935 (UK) 4250059689350 1470 g 188 x 231 x 92 mm	