

CAM B25M500POE



5MP Outdoor Fixed Bullet IP POE

Manufacturer: [AMIKO](#)

Description

Camera

- Image Sensor 1/2.7" Foshan FH8856 CMOS Sensor
- Resolution 5MP
- Effective Pixels: 2592 (H) x 1944 (V)
- Compression H.264/H.264+/H.265/H.265+/MJPEG
- TV System PAL/NTSC
- Electronic Shutter Time Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
- Minimum Illumination 0.005Lux
- S/N Ratio ?52dB
- Scanning System: Progressive
- Video Output Network

Lens

- Focus Length: 3.6mm
- Focus Control: Fixed
- Lens Type: Fixed
- Pixels: 5MP

Night Vision

- Infrared LED: 42μ x 2PCS
- Infrared Distance 25m
- IR Status: Auto Control
- IR Power On: Auto Control

Network

- Ethernet: RJ-45 (10/100Base-T)
- Protocol: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
- ONVIF: support ONVIF 2.4
- P2P: yes, Support QR Code
- POE Internal,
- Video Delay 0.3S (Within the Lan)
- Main Stream 1 2592*1944@20fps>
- Main Stream 2 2560*1920@20fps>
- Main Stream 3 2560*1440@25fps>
- Main Stream 4 1920*1080@25fps>
- Sub Stream 1 1280*720@20fps>
- Sub Stream 2 720*480@20fps>
- Sub Stream 3 352*288@20fps>
- IE Brower IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12)
- Smart Phone: iPhone, iPad, Android, Android Pad

Camera Features

- Day/Night: Color/ B&W (IR-CUT)
- Image Config: Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
- Corridor Pattern: Support
- BLC: Support
- WDR: Support
- Motion Detection: Support
- Privacy Masking: 3 Rectangular Zone
- Recording Mode: NVR/CMS/Web

Interface

- SD Card Slot: Internal, Max 512GB

General

- Housing: Metal, IP66
- Anti-cut Bracket
- IR Cut Filter
- Operation Temperature: -20? ~ +60? RH95% Max
- Storage Temperature: -20? ~ +60? RH95% Max
- Power Source: DC12V±10%, 950mA
- Dimension:186(W) x 75(H) x 71(D)mm
- Weight: 500g