

CAM KIT5500



5 Mpix, 4 x Dome Sony Starvis camera

Manufacturer: [AMIKO](#)

Description

5 Megapixel Dome camera

- Image Sensor: 1/2.8" CMOS sensor
- Resolution: 5MP Sony Starvis camera
- Max Resolution: 2592(H)*1944(V)
- Compression: H.264/H.264+/H.265/H.265+/-
- TV System: JPEG/AVI /MJPEG / PAL/NTSC
- Video Output: Network

LENS Type

- Focus Length: 3.6mm
- Focus Control: Fixed
- Lens Type: Fixed
- Pixels: 5M Pixels

Night Vision

- Infrared LED 14? x 18PCS
- Infrared Distance: 20M
- IR Status: Auto Control
- IR Power: On Auto Control

***NEW* Surveillance Systems: CAM KIT5500**

NVR 4CH PoE 4k HD

- Main Processor ARM Cortex A7 Quad coreProcessor
- Operating System Embedded LINUX

Video

- Input 9 Channel (IP Camera/Wired IP Camera), Support 2592x1944, 2048x1536,1920×1080,1280×960, 1280×720
- Output 1 VGA, 1 HD (max 3840×2160/30Hz)

Audio

- Input / Output 1 Port RCA(Linear, 1k)
- Audio Bit Rate 64kbps
- Audio Compression standard G711u, G711a, G726

Alarm

- Sensor Input: NO
- Output: NO
- Motion Detection 9 Channel, MD Zones: 396 (22 × 18)
- Trigger Events Recording, Email, FTP, Snapshot, Buzzer and Screen, Tips, alarm output

Network

- Interface: 1 RJ45 10M/100M Adaptive Ethernet Interface
- Incoming Bandwidth: 80MB
- Network Functions TCP/CP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP, p2p
- Onvif Version Support: Onvif 2.4
- Web Browser IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
- CMS Software Support: Windows 7/ Windows 8/Windows 10
- Smart Phone iPhone, iPad, Android, Android Pad

Storage

- Interface Type: 1 SATA Hard Disk Interface (2.5"/3.5" SATA)
- Capacity: up to 8TB capacity (HDD not included)