

CAM XVR420



16CH XVR 5in1

Manufacturer: [AMIKO](#)

Description

Video:

- Input: Analog: 4*(1920*2160 4*8fps)
- Analog+Network: Analog+Network:2*Analog+7*network(Max 5MP)
- Network: 16*5MP/4MP/3MP/1080P/960P/720P(Total incoming bandwidth ?48M)
- Input: 4CH BNC
- Signal Type: Analog/AHD/CVI/TVI 2.0/Network
- Output :1HD,1 VGA

Audio:

- Input: 2 Channel, RCA
- Output: 1 Channel, RCA

Display:

- VGA: Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
- HD Output: Resolution: 1920 × 1080P/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768/60Hz
- Display Split: 9 Channel/4 Channel / 1Channel
- Privacy Masking: 3 Rectangular Zones (Each camera)
- OSD: Camera title, Time, Video loss, Alarm, Motion detection, Recording

Network:

- Interface: 1 RJ45 10M/100M Adaptive Ethernet Interface
- Network Functions:TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP, RTCP
- DDNS: Dyndns, No-ip, Oray,

***NEW* Surveillance Systems: CAM XVR420**

- Web Browser: IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
- CMS Software: Support Windows 7/ Windows 8/Windows 10
- Extra Stream: CIF(1~25fps)
- Smart Phone: iPhone, ipad, Android ,Android pad

Hard disk driver:

- Interface Type 1 SATA Interface
- Capacity: 1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)

Physical specifications:

- USB Interface: 2 USB 2.0 Interfaces
- Power consumption: DC 12V ?6W (Without Hard Disk)
- Working Environment: -10~55?/10~90%
- Dimension (W×D×H): 260*215*43 (mm)
- Weight: 2kg (Without HDD)