

## HDMI ST0405



1x2 HDMI splitter 4K, 2K AND 3D

Manufacturer: [Daxis](#)

Description

### Introduction

This 1x2 HDMI splitter can connect Set-Top-Box, DVD player, laptop, PS3, PS4, XBOX, HDTV or other HD devices to two display devices via HDMI output interfaces and let the two display devices show the same picture.

1. 1 x HDMI 1.4b input, 2 x HDMI 1.4b output.
2. HDMI resolution up to 4K/30fs, support 3D.
3. Support 24 bit/Deep color 30 bit/36 bit.
4. Support Blu-ray DVD 24/50/60fs/HD-DVD/xvYCC.
5. Support audio format: DTS-HD/Dolby-trueHD/LPCM7.1/DTS/DOLBY-AC3/DSD
6. Support signal Re-Timing.
7. Use AWG26 HDMI 1.4b standard cable, input transmission distance up to 15m, output transmission distance up to 25m.
8. No loss of signal.
9. Power by DC 5V/1A external power adapter.

### GENERAL

Types	Splitter
Material	Metal
Input Port	AC 100-240V 50/60Hz (Charger)

Output Port	DC 5V 1A (Charger)
Interface	DC IN, 1 x HDMI IN, 2 x HDMI Out
HDMI Resolution	up to 4K/30fs
Video Color Format	24bit, 30bit, 36bit
Video Bandwidth	300MHz/10.2 Gbps
HDMI Audio Format	DTS-HD, Dolby- TrueHD, LPCM 7.1CH, DTS, Dolby- AC3, DSD
Input Cable Distance	<=15m AWG26 HDMI Standard Cable
Output Cable Distance	<=25m AWG26 HDMI Standard Cable
Input/ Output TMDS Signal	0.5~1.5Vp-p(TTL)
Input/ Output DDC Signal	5Vp-p(TTL)
Working Current Operating Temperature	600mA (Max) -10 to 55 Degree Celsius
Storage Temperature	-20 ~ 60 Degree Celsius
Operating Humidity	10 ~ 90 Percent RH (Non-condensing)
Storage Humidity	5 ~ 95 % RH (Non- condensing)
Power Plug Size	EU Plug 8.7x4.8x1.8cm
Weight	105g
Package Contents	1 x Power Adapter 1 x User Manual 1 x HDMI Splitter