REC MINI.HD H265



Full HD Digital Satellite Receiver HEVC

Manufacturer: AMIKO

Description

Main features :
- Conax Card reader embedded
- H.265 / HEVC decoding support
- Programmable up to 6000 channels TV and Radio
- Two High Speed USB 2.0 connections
- Ethernet connection & WiFi support via USB
- Youtube Videos
- Channel recording for external storage devices
- RSS Reader & Weather Forecast Function
- Timeshift Support
- Channel Recording & Timeshifting Simultaneously (Optional)
- Channel switching time less than 1 second
- True-color, User Friendly On-Screen Display (OSD)
- Full Picture In Graphic Function (PIG)
- Electronic Program Guide (EPG) for on-screen channel information
- Subtitle supported
- Parental control by channel or program
- Program and Channel information transfer from receiver to receiver
- Satellite Blind scan & Fast Scan support
- DiSEqC 1.0, 1.1, 1.2 & USUALS compatible
- Full HD (1080p) output for HDMI
- Games embedded
- Multi-language support
- Software upgrade support via USB, Network, OTA, RS232
- Standby power consumption : <0.5

Characteristics :
* Tuner & Demodulation :
- Tuner type : DVB-S / DVB-S2
- Input connector : F-Type, Connector, Female
- Signal level : -65 to -25 dBm
- LNB power & polarization : Vertical : + 13V / + 14V; Horizontal: + 18V / + 19V
- Current : Max 400mA (Overload protection)
- 22KHz Tone frequency : 22 ± 1KHz
- DiSEqC control : Version 1.0, 1.1, 1.2, USALS
- Demodulation : QPSK, 8PSK
- Input symbol rate : 2 - 45 Mbps,
- FEC : 1/2, 2/3, 3/4, 5/6, 7/8 and Auto

* MPEG TS A / V decoding :
- Transport Stream : MPEG-2, H.264, H.265
- Input rate : Max. 120Mbit / s
- Aspect Ratio : 4: 3, 16: 9, Letter Box
- Video decoding : MPEG-4 / H.265, SP @ L3 to ASP @ L5, AVC, HP @ level 4.1, MP @ level 4.1
- Video resolution : 720 * 480P / I, 720 * 576P / I, 1280 * 720p, 1920 * 1080i, 1920 * 1080p
- Audio decoding : MPEG-1/2, AAC-LC, HE-AAC, MP3, Dolby Digital
- Audio Mode : Left / Right / Stereo / Mono
- Sampling rate : 32, 44.1 and 48KHz

* System Resources :
- Processor : 800MHz CPU
- Flash Memory : 16MB
- DDR3 RAM : 256MB

* Power Supply :
- Input voltage : 12V DC
- Power Consumption : 24W Max
- Consumption in stand-by mode : <0.5W

* A / V & Data Input / Output :
- RCA jack : CVBS Video out, L & R audio out
- USB : 2x USB 2.0 High Speed slots
- S / PDIF : coaxial
- HDMI : VER1.4, Type A
- Ethernet: 10 / 100M RJ45
- RS232 : Jack-Type, Transfer rate 115.2Kbps, 9 pin D-sub type
- IR IN : Jack-Type, External IR sensor connection

* Physical specifications :
- Net Weight : 0.5KG
- Operating temperature : 0 ° C ~ + 45 ° C
- Storage temperature : -10 ° C ~ + 70 ° C
- Storage humidity : 5% ~ 95% RH (non-condensing)
- Size (W*H*D) : 144mm x 40mm x 110mm