

TAP DER115



1st IF SAT tap-off, 1 output. Tap loss -15dB

Manufacturer: [Fagor](#)

Description

MODEL		SPLITTERS					TAP-OFFS							
Reference		REP 304	REP 307	REP 400	REP 610	REP 616	DER 110	DER 116	DER 120	DER 126	DER 210	DER 216	DER 220	DER 226
Nr. of outputs		86281	86282	86283	86284	86285	86286	86287	86288	86289	86270	86271	86272	86273
Covered band	MHz						5 + 2300							
Tap Loss (a 0,5 dB)		dB					10	15	20	25	10	15	20	25
Through loss	5 - 47 MHz	—	—	—	—	—	10	15	20	25	10	15	20	25
	47 - 862 MHz	4	6,5	7,5	10,5	11	3	1,5	1,1	1	3,5	2,5	1,5	1
	860 - 2150 MHz	5,5	8	9,5	14,5	15,5	2,2	2,2	1,9	1,8	3,5	3	2,5	1,7
	2150 - 2300 MHz	6	10	10,5	15	16	2,2	2,2	2,2	2,1	4	3	3	2,1
Directional isolation	5 - 47 MHz	—	—	—	—	—	25	25	27	30	20	25	30	35
	47 - 862 MHz	—	—	—	—	—	24	24	25	27	20	22	25	35
	860 - 2150 MHz	—	—	—	—	—	23	23	23	24	15	22	22	28
	2150 - 2300 MHz	—	—	—	—	—	23	23	23	24	15	21	22	28
Output isolation	5 - 47 MHz	—	—	—	—	—	20	20	20	24	15	21	22	25
	47 - 862 MHz	20	20	21	22	24	—	—	—	—	40	45	60	22
	860 - 2150 MHz	21	21	21	22	22	—	—	—	—	30	35	45	22
	2150 - 2300 MHz	20	20	21	21	21	—	—	—	—	28	30	32	22
Return losses	5 - 47 MHz	—	—	—	—	—	—	—	—	—	—	—	—	—
	47 - 862 MHz	—	—	—	—	—	12	12	12	12	12	12	12	12
	860 - 2150 MHz	—	—	—	—	—	10	10	10	10	10	10	10	10
	2150 - 2300 MHz	—	—	—	—	—	8	8	8	8	8	8	8	8
Min. screening factor	5 - 862 MHz	—	—	—	—	—	—	—	—	—	—	—	—	—
	860 - 2150 MHz	20	20	21	20	21	—	—	—	—	28	30	32	22
Packing dimensions (10 u.)	mm	115/300					160 x 105 x 57		205 x 125 x 57		115 x 105 x 57		160 x 105 x 57	
Weight (10 u.)	Kg	0,50					0,60		1,10		0,50		0,60	