

## TAP DER410



1st IF SAT tap-off, 4 outputs. Tap loss -10dB

Manufacturer: [Fagor](#)

### Description

MODEL	TAP-OFFS									
	DER 410	DER 415	DER 420	DER 425	DER 615	DER 620	DER 625	DER 615	DER 620	DER 625
Reference	86274	86275	86278	86277	86278	86279	86330	86281	86282	86283
Nr. of outputs	4				6			8		
Covered band	MHz				5 + 2300					
Tap Loss (e 0.5 dB)	5 - 2300 MHz									
5 - 47 MHz	10	15	20	25	15	20	25	15	20	25
47 - 862 MHz	4	2	1	1	3,5	1,5	0,5	3,5	1,5	1
Through loss	4	2,5	1	1	4	2	1,5	4	2	1
860 - 2150 MHz	5	4	2	2	3	4,5	3,5	3	3,5	2
2150 - 2300 MHz	5,5	4,5	3	2	5,5	5	5	5,5	3,7	2,5
Directional isolation	5 - 47 MHz									
47 - 862 MHz	25	30	35	45	25	30	30	25	30	30
860 - 2150 MHz	27	28	30	35	22	24	23	22	24	23
2150 - 2300 MHz	25	25	25	25	22	25	25	22	25	25
5 - 47 MHz	23	23	23	23	22	24	24	23	24	24
Output isolation	47 - 862 MHz									
860 - 2150 MHz	22	22	22	22	22	22	20	22	22	22
2150 - 2300 MHz	21	21	22	22	22	22	20	22	22	22
Return losses	5 - 862 MHz									
860 - 2150 MHz	10									
Min. screening factor	5 - 862 MHz									
860 - 2150 MHz	65									
Packing dimensions (10 u.)	mm					mm				
Weight (10 u.)	Kg					Kg				